

## DESCRIPTION

Johnstones Steel & Cladding Topcoat is specially formulated to provide long lasting protection against corrosion on metal substrates. It is UV resistant and has good water resistance for all round weather protection. Ideally use over Johnstone's Quick Dry Zinc Phosphate Primer for lasting corrosion protection.

## RECOMMENDED USES



Plastisol cladding, suitably prepared steel and other metallic surfaces.

## SPECIAL PROPERTIES

UV resistance and good weather resistance for all round weather protection.

## COLOUR RANGE

Available in a range of colours via our Tinting System.

## FINISH

Semi-gloss.

## VOLUME SOLID

50%.

## COVERAGE



Johnstone's Semi-Gloss Topcoat will cover at the rate of approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

## DRYING TIME



Recoat after 16–24 hours under normal drying conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

TC2 Thinner and Cleaner.

## VOC CONTENT

HIGH VOC CONTENT 25–50%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 500g/l (2010).  
This product contains max 500g/l VOC.

## FILM THICKNESS

Wet: 100µm, dry: 50µm.

## SIZE

5 Litre

## PREPARATION

**Steel:** Prepare surface and prime accordingly. If overcoating an existing paint ensure the surface is clean and dry.

**Cladding:** Clean thoroughly with Johnstones Cleaner & Degreaser after removing all loose and flaking paint, salts etc. Wash down with clean water. All bare areas of steel/aluminium must be suitably prepared and spot primed with Quick Dry High Build Zinc Phosphate Primer or Steel and Cladding Coatings 2 Pack Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice and free Johnstone's Trade datasheets, call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Stir thoroughly before use. Apply by brush or roller. If more than one can of a colour is to be used in the same area, intermix before use.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with TC2 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.