

## DESCRIPTION

Johnstone's Universal Primer is a solvent-borne primer formulated for interior and exterior use on new or bare wood, metal, plaster and masonry. Based on an alkyl resin, it is particularly suitable for multi-surface work.

## RECOMMENDED USES



Suitable for interior and exterior use.

## TYPE OF SUBSTRATE

Wood, metal, plaster and masonry.

## COLOUR RANGE

White and Red Oxide.

## FINISH

Not applicable.

## VOLUME SOLID

61%

## COVERAGE



Approximately 12 square metres per litre, depending on the nature and porosity of the surface.

## DRYING TIME\*



Recoat after 16–24 hours under normal drying conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

## CLEANER

White spirit.

## VOC CONTENT

High VOC content 25–50% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010). This product contains max 300g/l VOC.

## FILM THICKNESS

Wet: 85µm, dry: 52µm.

## KEY PROPERTIES

- Suitable for use on wood, metal and dry plaster.
- Especially suitable for multi-surface work.

## PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel remove all millscale and rust. Wear a suitable face mask if creating dust. Special precautions should be taken during the surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For additional information and free Johnstones Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Stir well. Easy to apply by brush or roller. On woodwork apply by brush and work well into the grain. Do not apply over polystyrene surfaces.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- **FLAMMABLE**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition - No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - **DO NOT USE SOLVENT OR THINNERS.**
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas - walls, floors or ceilings - or in confined spaces.
- If swallowed seek medical advice immediately and show this container or label.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

## SIZES

1 Litre, 2.5 Litre, 5 Litre.