

# Anti Slip Additive

# DESCRIPTION

Johnstone's Trade Anti-Slip Additive is a silica quartz based additive powder to give smooth floor coatings a tough and durable slip resistant performance.

# RECOMMENDED USES



For use with all Johnstone's Trade Floor Coatings.

# SPECIAL PROPERTIES

Provides an anti-slip surface. Very tough, durable additive.

# COLOUR RANGE

Not applicable.

# FINISH

# VOLUME SOLID

Not applicable.

100%

#### COVERAGE



Approximately 0.5–2kg per 5 litre tin or sprinkle at a rate of 0.5–1kg per square metre.

# FILM THICKNESS

Wet: not applicable, dry: not applicable.

# DRYING TIME

Not applicable.

# TRANSPORTATION & STORAGE

Not applicable.

# THINNER

Not applicable.

# **VOC CONTENT**

Not applicable.

#### KEY PROPERTIES

- For use with all Johnstone's Trade Floor Coatings
- Very tough and durable
- Provides a slip resistant surface

#### PREPARATION

Not applicable.

# APPLICATION

Add directly to the paint, just before use, at the rate of 0.5kg to 2kg per 5 litre tin of paint and mix thoroughly. The actual weight of Anti-Slip Additive used will depend on the degree of slip resistance required. Alternatively, sprinkle directly onto wet application of the floor coating at a rate of 0.5kg to 1kg per square metre. When the coating is dry, any excess Anti-Slip Additive should be swept away and a further 1 or 2 coats of the floor coating applied to seal the aggregate thoroughly, although this may reduce the slip resistance. For more information and free Johnstone's Trade datasheets call 01924 354678 or visit www.johnstonestrade.com.

### CLEANING

Not applicable.

# PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available: www.johnstonestrade.com or call 01924 354354

#### SIZE

1.5kg

