

STORMSHIELD

EWI & RENDER

High Performance
Basecoat

Silicone Mineral
Thin Coat Render

SILICONE MINERAL THIN COAT RENDER

Johnstone's Silicone Mineral Thin Coat Render is a cement based product that can be applied in low temperatures. No primer is required, allowing it to be applied directly onto a basecoat. The cement based formulation sets rather than cures, making the product shower proof very quickly.

AVAILABLE AT JOHNSTONE'S DECORATING CENTRES

ASK IN-STORE FOR DETAILS

FEATURES AND BENEFITS

No primer required – the product can be applied directly onto the basecoat, increasing the speed of the application.

Apply in low temperatures – can be applied in zero degree temperatures, removing the limitations of seasonal weather.

Fast drying – sets in 2-3 hours increasing productivity on the job and the risk of wash off.

Silicone Additive – removes risk of water contamination impacting the colour of your render.

FINISH	APPLICATION	SIZE	COVERAGE	TOUCH DRY	COLOUR
1.5MM	TROWEL OR MACHINE	25KG	10m ² PER 25KG	2-3 HOURS	WHITE, IVORY, COUNTRY CREAM, MUSHROOM, & PRINCESS GREY

APPLICATION



1. SMTCR is a two part product. Remove part A and part B from the tub prior to activation.



2. Thoroughly shake part A and pour it into the mixing tub.



3. Add part B.



4. Mix with a suitable paddle mixer for 2-3 minutes.



5. Allow to stand for 3 minutes, then mix for a further 2-3 minutes.



6. Apply using a stainless steel trowel or suitable spray equipment.



7. Cross trowel to ensure the minimum amount of material is applied to the correct thickness.



8. Finish with a plastic float, working the material in small circular motions.



