

Single Pack Primer



Johnstone's Trade Single Pack Primer is a fast drying, anticorrosive primer for use under a wide variety of conventional finishes. It has excellent anti-corrosive properties on properly prepared steel and good adhesion to pre-treated steel and aluminium. Suitable for use as part of a conventional anticorrosive paint system. Can be welded. Suitable as a holding primer.

RECOMMENDED USES



Priming of properly prepared steel and pre-treated aluminium.

SPECIAL PROPERTIES

Excellent anti-corrosive properties. Rapid drying.

COLOUR RANGE

Light Grey.

FINISH

VOLUME SOLID

Matt.

51%.

COVERAGE



Johnstone's Trade Single Pack Primer will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 100μm, dry: 50μm.

DRYING TIME



Recoatable after 4 hours under normal drying conditions.

TRANSPORTATION & STORAGE

To avoid risk of spillage, always store and transport in a secure upright position. STORE AWAY FROM HEAT AND FLAME.

THINNER

Thinner: Johnstone's Trade TC1

VOC CONTENT

EU limit value for this product (Cat A/i): 500g/l (2010). This product contains max 500g/l VOC



KEY PROPERTIES

- Anti-Corrosive
- · Quick drying

PREPARATION

Blast cleaned to SIS-Sa '2 1/2' minimum or mechanically to SIS-St 3 minimum. Previous suitable coats should be clean, dry and abraded if necessary. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Mix thoroughly before use. Suitable for application by brush, roller or spray. For application by brush or roller, thin with up to 5% TC1 Thinner and Cleaner if required. For application by spray, thin with 10–20% TC1 Thinner and Cleaner for conventional spray and 0–15% TC1 Thinner and Cleaner for airless spray.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with Johnstone's Trade TC1 Thinner and Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre.

