

Microbarr Anti Bacterial Acrylic Eggshell



DESCRIPTION

Johnstone's Trade Microbarr Anti Bacterial Acrylic Eggshell is a high performance, tough acrylic resin based interior coating, formulated to assist in the fight against hospital acquired infections, caused by harmful bacteria. Formulated using Silver Ion technology, Johnstone's Trade Microbarr Anti Bacterial Acrylic Eggshell is proven to actively inhibit MRSA and E-Coli.

RECOMMENDED USES



Developed using Silver Ion Technology to inhibit bacteria and provide a tough, washable finish. For interior use in areas of high traffic and when hygiene protection is required.

SPECIAL PROPERTIES

Tough, durable Eggshell formulated to assist in the fight against infections caused by harmful bacteria.

COLOUR RANGE

Brilliant White, Magnolia. Available in a range of colours via the Johnstone's tinting system.

FINISH

VOLUME SOLID

Eggshell.

36%

COVERAGE



Johnstone's Trade Microbarr Anti Bacterial Acrylic Eggshell will cover approximately 12 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 83μm, dry: 30μm.

DRYING TIME



Touch dry in 1-2 hours. Allow 3-4 hours before applying a second coat if required. Do not apply when air or surface temperature is below 10°C or in damp conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST

THINNER

Thinner: Clean Water.

VOC CONTENT

EU limit value for this product (Cat A/a): 30 g/l (2010) This product contains max 3 g/l VOC $^{\circ}$



KEY PROPERTIES

- Inhibits growth of MRSA and E-Coli
- Contains Silver Ion Technology
- Proven to actively inhibit bacteria

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Trade primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a precoat of Johnstone's Trade Ultra Primer Sealer as directed. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets, call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Johnstone's Trade Microbarr Anti-Bacterial Acrylic Eggshell thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/ transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre.

