



# AQUA WATER BASED TRIM

PAINT TO BE PROUD OF



The Johnstone's Aqua System range of trim coatings offer a high quality water based alternative to traditional solvent based products. They feature similar application and finish qualities to a traditional solvent based product along with the outstanding benefits of water based coatings. The Aqua range is quick drying, low odour, durable and offers a superior finish compared to other water based products.

## Features and Benefits

- Applies more like a solvent based finish** → A longer wet edge time allows for easier application to offer a superior finish
- Quick drying** → Undercoat can be recoated after 4-6 hours allowing for the system to be applied in a day
- Water based** → Low odour and more friendly to the environment
- Improved yellowing** → Stays whiter for longer

## Product Data

Product Name	Finish	Colours	Sizes	Coverage	Recoat
Aqua Water Based Gloss	Gloss	16,000 colours	1ltr/2.5ltr/5ltr	10-12 sq metres/litre	4-6 hours
Aqua Water Based Satin	Satin	16,000 colours	1ltr/2.5ltr/5ltr	10-12 sq metres/litre	4-6 hours
Aqua Water Based Undercoat	Matt	16,000 colours	1ltr/2.5ltr/5ltr	10-12 sq metres/litre	4-6 hours



For further information and advice please call 01924 354354  
 Find out more at: [www.johnstonestrade.com](http://www.johnstonestrade.com)



# AQUA WATER BASED TRIM

PAINT TO BE PROUD OF



**Where to use AQUA** - Suitable for interior use over skirting, wooden trim, doors, and other softwood, hardwood and plywood surfaces. Also suitable for use over metal.



## Why use AQUA?

### Improved Application

- Applies more like a solvent based paint with a longer wet edge time than standard water based trim products.

### High Quality Finish

- Delivers a superior finish more like a solvent based coating.

### Quick Drying

- Being a water based product, Aqua Undercoat and Topcoat dries within 4-6hrs allowing jobs to be completed to a high standard in just one day.

### Improved Yellowing

- Offering increased durability with a finish that stays whiter for longer.

### Low Odour

- Minimal odour means areas can be brought back in to use quicker than before.




## System and Application Tools

The ideal system to use is as follows:

- 1 - Apply Aqua Water Based Undercoat. Dry within 4-6hrs
- 2 - Apply 2 coats of Aqua Water Based Gloss or Satin. Dry within 4-6hrs

**Application Tool:** Roll on with Fat Hog Microfibre and then lay-off with a Fat Hog Duroc Synthetic Brush

**Cleaning Equipment:** To maintain brushes, do not allow paint to dry out on bristles. Regularly wash in clean, cold soapy water throughout use. Following prolonged use, clean with Clean Spirit



For further information and advice please call 01924 354354  
Find out more at: [www.johnstonestrade.com](http://www.johnstonestrade.com)