

DESCRIPTION

Johnstone's Woodworks Decking Stain provides 3 years all weather protection to new and previously stained decking and cladding. The wax enriched formulation gives a one-step water repellent finish that is quick drying, long lasting and helps resist cracking, peeling and fading. Adds a coat of colour and dries to give a tough matt finish whilst protecting against mould and fungal growth.

AVAILABLE IN

2.5 Litre.

COLOUR RANGE

Rich Teak, Spanish Cedar, Natural Oak, Chestnut Brown.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Decking and cladding.

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface being stained.

DRYING TIME



Touch dry 1-2 hours.
Recoatable 4 hours.
Allow longer in adverse conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Ensure lid is sealed tightly. Protect from frost.

CLEANER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30-7.99%
VOC'S (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (cat A/e): 150g/l (2007) / 130g/l (2010).
This product contains max 10g/l VOC.

PREPARATION

Ensure the surface to be stained is clean, dry and free from dust, grease, polish or any other coatings such as paint or varnish. Nail and screw heads in joinery should be set below the surface and concealed by a suitable wood filler.

BARE or NEW WOOD:

Softwood should first be treated with Johnstone's Woodworks All Purpose Preserver.

PREVIOUSLY PAINTED OR VARNISHED WOOD:

Remove all traces of previous coatings before staining. Use a Paint & Varnish Stripper to remove traces of previous treatment then treat as for bare or new wood. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further information contact Technical Advisory on 01924 354354.

APPLICATION



Stir well before use. Apply evenly with the use of a brush or pad working well into the timber and along the grain. Apply two coats to bare and previously preservative treated timber. Redecoration requires one coat.

CLEANING



Remove as much product as possible from the application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly after use. Do not empty products into drains or watercourses. Some local authorities' have special facilities for the disposal of waste coatings.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), 1,2-benzisothiazol-3(2H)-one and othilinone (ISO). May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.