

DESCRIPTION

Johnstone's Ultra Primer & Finish is a high performance, quick drying, alkali resisting primer and finish that is manufactured from high quality pigments and tough acrylic resin with enhanced stain blocking properties. It primes and seals porous surfaces as well as offering great adhesion to difficult to apply surfaces including galvanised metal, to provide a fast drying, low odour, sprayable and wipeable finish coat. Provides a great basecoat for Johnstone's Acrylic emulsions.

RECOMMENDED USES

Suitable for interior use.

SPECIAL PROPERTIES

Rapid drying. Can be used over multiple substrates and hard to adhere to including galvanised metal.

COLOUR RANGE

Brilliant White.

FINISH

Eggshell.

VOLUME SOLID

45%.

COVERAGE

Johnstone's Ultra Primer & Finish will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Touch dry in 30 minutes.

Recoat after 3 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position.

THINNER

Clean water

VOC CONTENT

LOW VOC CONTENT 0.3 -7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 30g/l (2010).

This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 45µm.

SIZE

10 Litre.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Surfaces should be suitably prepared before application. Rub down previously painted surfaces with fine waterproof abrasive paper. Hard wall plasters should be scored with coarse glasspaper. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets, call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION

Stir well before use. Apply one full coat, brushing firmly into the surface. Porous surfaces should be sealed with a first coat of Ultra Primer & Finish thinned with up to 20% clean water. Allow 3 hours to dry under normal conditions before applying the required paint finish. Ultra Primer & Finish can be applied by airless spray. Size 12-15 thou, 1,600-1,800 PSI. Allow fresh plaster to dry thoroughly before application. Do not apply when air or surface temperature is below 10°C.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.