

DESCRIPTION

Woodworks Knotting Solution is a quick drying solution suitable for preventing resinous sap bleeding through knots in wood and discolouring paint or varnish finishes. Conforms to BS1336.

AVAILABLE IN

250ml

RECOMMENDED USES



Suitable for interior & exterior use.

TYPES OF SUBSTRATE

Interior and exterior bare timber with knots, doors, door frames, furniture and railings.

COVERAGE



Woodworks Knotting Solution will cover approximately 10sqm per litre, depending on the nature and porosity of the timber.

DRYING TIME



Can be over coated after 30 minutes.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position.

STORE AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION.

CLEANER

Methylated Spirit.

VOC CONTENT

VERY HIGH VOC CONTENT MORE THAN 50% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/h): 750 g/l (2010).

This product contains max 750 g/l VOC.

PREPARATION

Ensure that the wood to be treated is thoroughly clean and dry and free from resinous matter or loose particles. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Rub down the surface with abrasive paper to provide a key. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Shake well before use. Using a brush or lint free cloth, apply a liberal coat and leave to dry. Apply a full coat with the minimum if brush work. Touch dry in 5-10 minutes. If a second coat is required, this can be applied after 30 minutes, but brushing must be kept to a minimum to avoid working-up the underlying film. Will cover approximately 10 square metres per litre.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with Methylated Spirit. Replace lid firmly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- PAINT UN1263
- HIGHLY FLAMMABLE
- Keep away from sources of ignition - No smoking.
- Keep container tightly closed in a cool, well ventilated place.
- In case of insufficient ventilation, wear suitable respiratory protective equipment.
- Use only in well ventilated areas.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - **DO NOT USE SOLVENT OR THINNERS.**
- If swallowed, seek medical advice immediately and show this container or label.
- Do not empty into drains.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.