

Durable Quick Dry Polyurethane Varnish

DESCRIPTION

Woodworks Durable Quick Dry Polyurethane Varnish is a specially formulated water based varnish for use on doors, windows, furniture and all interior smooth planed timber. It provides a hardwearing finish that enhances the natural beauty of wood.

AVAILABLE IN

750ml and 2.5 litre sizes.

COLOUR RANGE

Clear Gloss and Clear Satin.

RECOMMENDED USES




Suitable for interior use.

TYPES OF SUBSTRATE

Quality timber, doors, window frames, furniture and all interior smooth planed timber.

COVERAGE



Approximately 12 square metres per litre depending on the nature and porosity of the surface being varnished.

DRYING TIME



Touch dry in 1 hour.
Recoat after 4 hours. Conditions of high humidity will prolong drying time.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

THINNER

Water.

VOC CONTENT

LOW VOC CONTENT 0.30-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/e): 130g/l (2010). This product contains max 80g/l VOC.

PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Do not prepare the surface using steel wool. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



Stir Quick Dry Polyurethane Varnish thoroughly before use. Apply two or more coats of varnish evenly, by brush along the grain paying particular attention to the end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with up to 10% clean water, followed by two further coats of undiluted varnish. Sand down lightly between coats. Do not apply when temperature is below 10°C. This product is not suitable for application over ferrous metal.

Note: Quick Dry Polyurethane Varnish is naturally milky in appearance when wet. This will disappear when completely dry. The final colour will depend on the original colour of the wood and the number of coats applied. It is advisable to test for colour in an inconspicuous area first.

CLEANING



Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents to a Waste Disposal Site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.