

DESCRIPTION

A silica quartz based additive powder to give smooth floor paints a tough and durable slip resistant performance. Ideal for use in areas prone to slip risk.

RECOMMENDED USES

For use with all Johnstone's Floor Coatings.

SPECIAL PROPERTIES

Provides an anti-slip surface. Very tough, durable additive.

COLOUR RANGE

Not applicable.

FINISH

Not applicable.

VOLUME SOLID

100%

COVERAGE

Approximately 0.5–2kg per 5 litre tin or sprinkle at a rate of 0.5–1kg per square metre.

DRYING TIME

Not applicable.

TRANSPORTATION & STORAGE

Not applicable.

THINNER

Not applicable.

VOC CONTENT

Not applicable.

FILM THICKNESS

Wet: not applicable, dry: not applicable.

SIZE

1.5kg

PREPARATION

Not applicable.

APPLICATION

Add directly to the paint, just before use at the rate of 0.5–2kg per 5 litre tin of paint and mix thoroughly. Weight of product used will depend on the degree of slip resistance required. Alternatively sprinkle directly onto wet application of the floor coating at a rate of 0.5kg to 1kg per square metre. When the coating is dry, any excess Anti Slip Additive should be swept away and a further 1 or 2 coats of the floor coating can be applied to seal the aggregate thoroughly, although this may reduce the slip resistance.

CLEANING

Not applicable.

PRECAUTIONS

- Do not breathe the dust.
- Use only in well ventilated areas.
- Avoid contact with eyes.
- In case of contact with eyes, rinse immediately with plenty of water and if necessary seek medical advice.
- Keep out of the reach of children.