

**DESCRIPTION**

A quick drying primer with excellent adhesion properties making it ideal for use on problem areas such as glazed tiles and smooth melamine surfaces. Based on a water based acrylic primer for maximum durability. Also suitable for priming more conventional substrates such as wood and metal etc.

**RECOMMENDED USES**

Primes melamine, powder coat, glazed tiles, matt tiles, quarry tiles, glass and suitably prepared ferrous and non-ferrous metals.

**SPECIAL PROPERTIES**

Excellent adhesion to non-porous surfaces. Quick drying and low odour.

**COLOUR RANGE**

Brilliant White.

**FINISH**

Matt.

**VOLUME SOLID**

38%

**COVERAGE**

Johnstone's Multi-Surface Primer will cover at the rate of approximately 13–15 square metres per litre depending on the nature and porosity of the surface being painted.

**DRYING TIME**

Touch dry in 30 minutes.  
Recoat after 4–6 hours.

**TRANSPORTATION & STORAGE**

To avoid the risk of spillage always store and transport in a secure upright position. PROTECT FROM FROST.

**THINNER**

Water.

**VOC CONTENT**

LOW VOC CONTENT 0.30–7.99%.  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 140g/l (2010).  
This product contains max 10g/l VOC.

**FILM THICKNESS**

Wet: 80µm, dry: 30µm.

**SIZE**

1 Litre and 2.5 Litre.

**PREPARATION**

All surfaces to be painted should be clean, dry and free from loose and flaking material. Exposed nail and screw heads should be treated with Johnstone's Water Based Metal Primer. Lightly sand the surface with a fine waterproof abrasive paper and wipe clean. Wear a suitable face mask when dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory on 01924 354354.

**APPLICATION**

Stir well before use. Suitable for application by brush. Do not apply when air or surface temperature is below 5°C.

**CLEANING**

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

**PRECAUTIONS**

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.