

## DESCRIPTION

A pre-treatment for galvanised steel which converts the surface nature to ensure the subsequent adhesion of a wide range of coatings.

## RECOMMENDED USES

A pre-treatment for galvanised steel to ensure adhesion of topcoat.

## SPECIAL PROPERTIES

Converts the surface nature of galvanised steel.

## COLOUR RANGE

Blue.

## FINISH

Matt.

## VOLUME SOLID

Not applicable.

## COVERAGE



Johnstone's Mordant Solution will treat approximately 15 square metres per litre.

## DRYING TIME

30 minutes (minimum), 24 hours (maximum).

## TRANSPORTATION &amp; STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

Not applicable.

## VOC CONTENT

Not applicable.

## FILM THICKNESS

Wet: not applicable, dry: not applicable.

## SIZE

5 Litre.

## PREPARATION

Ensure all oil and grease is removed from the surface to be treated by using Johnstone's Cleaner & Degreaser. Allow the surface to dry before application of subsequent coating.

## APPLICATION

Thoroughly work Johnstone's Mordant Solution into the surface using a brush ensuring all the surface changes colour (blackens). If no initial reaction takes place, then a second application may be required. Rinse with clean water and allow to dry.

## CLEANING

Not applicable.

## PRECAUTIONS

- IRRITATING TO EYES.
- Contains: Propan-2-ol.
- Use only in well ventilated areas.
- Vapours may cause drowsiness and dizziness.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of water.
- Wear suitable protective clothing, gloves and eye/face protection.
- If swallowed, seek medical advice immediately and show the container or label.
- Keep out of the reach of children.

## PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

