



DESCRIPTION

Johnstone's Performance Coatings Water Based Steel & Cladding Topcoat has been specially formulated for the use on new, pre-treated, weathered, or previously painted metal and plastisol cladding. With its water-based technology it provides a quick drying, sprayable solution in a satin finish to transform cladding and other metal structures to offer up to 8 years protection.

RECOMMENDED USES



Plastisol cladding, suitably prepared steel and other metal surfaces.

COLOUR RANGE

Available in 10,000 colours via the Johnstone's Tinting System.

FINISH

Satin.

VOLUME SOLID

45%

COVERAGE



Will cover approximately 11 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Recoat after 8 hours. High humidity and low temperatures will prolong drying times.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. Lift with care - gross weight does not exceed 8 kilograms.

THINNER

Water.

VOC CONTENT

MEDIUM VOC CONTENT 8-24.99%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).
This product contains max 110g/l VOC.

FILM THICKNESS

Wet: 90-130µm, dry: 40-60µm.

SIZE

5 Litre

PREPARATION

CLADDING: All surfaces to be painted should be clean, dry and free from loose and flaking material, cleaned using Johnstone's Cleaner and Degreaser and allowed to dry.

All bare areas of steel/aluminium must be suitably prepared and spot primed using Johnstone's Water Based Metal Primer.

STEEL: Prepare surface and prime using Johnstone's Water Based Metal Primer. If overcoating an existing paint ensure the surface is clean and dry. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir thoroughly before use. Suitable for application by brush, roller or spray. Do not apply in temperatures below 8°C or externally when rain is imminent. If more than one tin of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request. If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Do not breathe spray. Wear respiratory protection.
- Safety data sheet available for professional user on request.