

DESCRIPTION

Johnstone's Stormshield Self-Cleaning Masonry has been formulated using groundbreaking nano technology in order to give an extremely smooth and dirt resisting finish. Suitable for application to exterior cement rendering, rough cast, brick and concrete, the coating is also highly flexible.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Cement rendering, rough cast, brick and concrete.

COLOUR RANGE

Tintable to a range of colours available in the Johnstone's Trade Colour Card.

FINISH

Matt

VOLUME SOLID

30%

COVERAGE



Johnstone's Stormshield Self-Cleaning Masonry will cover approximately 10 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 12 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **PROTECT FROM FROST.**

CLEANER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 40g/l(2010).

This product contains max 15g/l VOC.

FILM THICKNESS

Wet: 100µm, dry: 30µm

KEY PROPERTIES

- Unique nano particle technology
- Flexible, dirt resisting smooth finish
- 15 years life expectancy

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Treat fungal or algal growth with Fungicidal Wash as directed. Seal absorbent surfaces with a coat of Stormshield Self-Cleaning Masonry, thinned up to 10% with clean water. Wear a suitable face mask when creating dust. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or long pile roller. Do not apply in temperatures below 5°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.

SIZES

5 Litre, 10 Litre