

DESCRIPTION

Johnstones Stain Block Primer is suitable to contain unsightly stains caused by nicotine, smoke, marker pen, wax crayon, graffiti, tannin and bitumen. It provides a tough durable matt coating which prevents stains bleeding through from the substrate. Stain Block Primer will not prevent stains caused by water damage unless the fault has been eradicated, and the substrate allowed to dry. Can be overcoated with water based emulsions.

RECOMMENDED USES

Primer for use on plaster, masonry and wood to cover unsightly stains.

SPECIAL PROPERTIES

Tough durable matt coating which prevents stains bleeding through from the substrate. One coat coverage. Can be used over water stains, grease, nicotine, rust, graffiti and ink.

COLOUR RANGE

White.

FINISH

Matt.

VOLUME SOLID

42%

COVERAGE

Johnstone's Stain Block Primer will cover at the rate of approximately 8 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

Under normal conditions touch dry and recoatable after 2-4 hours,

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

White Spirit.

VOC CONTENT

HIGH VOC CONTENT 25-50%.

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/g): 350g/l (2010).

This product contains max 350g/l VOC.

FILM THICKNESS

Wet: 125µm, dry: 53µm.

SIZE

1 Litre and 5 Litre.

PREPARATION

All surfaces should be clean, dry and free from grease. Remove any crazed or flaking paint. Rub down with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION

Stir thoroughly before use and apply by brush or roller, covering the stain and a surrounding area of 20cm to ensure maximum containment. Heavily soiled areas may require additional coats.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Brush Cleaner. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or air-fed respiratory protective equipment.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.