

# Quick Dry Polyurethane Floor Varnish

## DESCRIPTION

Woodworks Quick Dry Polyurethane Floor Varnish has been specially formulated for use on all interior timber floors and can also be used over cork tiles. This product provides a hardwearing, durable finish that enhances the natural beauty of the wood. This special formulation is suitable for application over previously varnished or stained surfaces. Provides excellent scratch resistance.

## AVAILABLE IN

2.5 litre and 5 litre sizes.

## COLOUR RANGE

Clear Gloss and Clear Satin.

## RECOMMENDED USES



Suitable for interior use.

## TYPES OF SUBSTRATE

Interior timber floors and cork tiles.

## COVERAGE



Approximately 18 square metres per litre depending on the nature and porosity of the surface being varnished.

## DRYING TIME



Touch dry in 1 hour.  
Recoat after 2–4 hours.  
Heavy foot traffic can be allowed after 16–24 hours, under normal conditions.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. PROTECT FROM FROST.

## THINNER

Water.

## VOC CONTENT

LOW VOC CONTENT 0.30–7.99%  
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution. EU limit value for this product (Cat A/i): 140g/l (2010). This product contains max 80g/l VOC.

## PREPARATION

Ensure all surfaces to be varnished are sound, clean, dry and free from dust, grease, polish or any other surface contaminant. Remove any flaking or cracked varnish. Sound, existing varnish should be rubbed down with fine waterproof abrasive paper, rinsed thoroughly and allowed to dry. Do not prepare the surface using steel wool. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

## APPLICATION



Stir Quick Dry Polyurethane Floor Varnish thoroughly before use. Apply two or more coats of varnish evenly, by a good quality brush along the wood grain as required, paying particular attention to the end grain. Do not overlap the brush strokes. On bare or new wood the first coat can be thinned with up to 10% clean water, followed by two further coats of undiluted varnish. Sand down lightly between coats. Do not apply when temperature is below 10°C, or when rain or snow are imminent. This product is not suitable for application over ferrous metal. For best results use a good quality synthetic brush.

## CLEANING



Remove as much product as possible from brushes before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.