



# Quick Dry Polyurethane Flortred

PAINT TO BE PROUD OF

## DESCRIPTION

Johnstone's Quick Dry Polyurethane Flortred has excellent durability compared to conventional solvent based single pack floor coatings. It is durable to wear, scratches, oil and grease spillages and is suitable for light wheeled traffic. It is suitable for interior and exterior\* use in light to medium traffic areas such as domestic floors, commercial facilities and light use factories and warehouses. The coating is ideal in areas where a quick drying, low odour floor coating is needed for areas that need to be brought quickly back in to use. To further boost the slip resistance of Johnstone's Quick Dry Polyurethane Flortred, use with Johnstone's Anti-Slip Additive.

\*Suitable for exterior use to highlight walkways, car parks spaces and other markings. Not suitable for use on large external areas.

## RECOMMENDED USES



For light to medium traffic areas.  
\*On area's subject to light traffic.

## SPECIAL PROPERTIES

Contains polyurethane.

## COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

## FINISH

Semi-gloss.

## VOLUME SOLID

44%.

## COVERAGE



Approximately 10 square metres per litre depending on the porosity of the substrate.

## DRYING TIME



Recoat after 10 hours under normal conditions. Conditions of high humidity can slow down the drying time.

## TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

## THINNER

Clean water.

## VOC CONTENT

MEDIUM VOC CONTENT 8-24.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 140g/l (2010). This product contains max 95g/l VOC.

## FILM THICKNESS

Wet: 100-125µm, dry: 55µm.

## SIZE

5 Litre.

## PREPARATION

Ensure the surface to be painted is sound, clean, dry and free from all loose and friable material. An effective damp-proof membrane is recommended to prolong the life of the coating. New concrete floors should be allowed to mature and thoroughly dry before painting. Porous surfaces must first be sealed with a thinned coat (by up to 10% by volume with water) of Quick Dry Polyurethane Flortred, taking care not to over-thin. Prime new or bare metal surfaces with Johnstone's Quick Dry Metal Primer.

Power floated floors should be suitably prepared using Johnstone's Acid Etch Solution, blast tracking or any other preparation method to create a porous surface. Do not use Johnstone's Quick Dry Polyurethane Flortred where silicate hardeners have been used, on Terazzo and Granolithic surfaces or substrates that are in cold and damp conditions. Do not use in areas subject to constant movement of car tyres or in heavy industrial or aggressive environments. For further advice and free Johnstone's Trade datasheets, call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

## APPLICATION



Stir well before use. On absorbent porous surfaces, the first coat should be thinned up to 10% by volume with water when necessary to ease brushing. Apply by brush or roller. Do not apply when temperatures are below or likely to fall below 8°C.

## CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

## PRECAUTIONS

- Contains: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, -[3-[3-(2H-benzotriazol-2-yl) derivatives, -[3-[3-(2H-benzotriazol-2-yl) derivatives and bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.



PAINT TO BE PROUD OF

For further information and advice please call 01924 354354  
Find out more at: [www.johnstonestrade.com](http://www.johnstonestrade.com)