

DESCRIPTION

Johnstone's Trade Jonmat is a high quality yet economical premium contract matt emulsion. It provides excellent coverage and has outstanding dry & wet opacity on interior walls and ceilings leaving a permeable breathable finish. Ideal for use on new plaster or plasterboard.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Broad walls, New plaster, Taped dry lined board, Skimmed plaster board, Range of boards including anti condensation and acoustic.

COLOUR RANGE

Brilliant White & Magnolia, plus over 7,000 colours via the Johnstone's Tinting System.

FINISH

Matt.

VOLUME SOLID

32%.

COVERAGE



Johnstone's Trade Jonmat will cover up to 16 square metres per litre depending on the nature and porosity of the surface being painted

DRYING TIME



Touch dry in 2-3hrs. Recoatable after 2-4hrs.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Clean Water.

VOC CONTENT

MINIMAL VOC CONTENT 0-0.29% VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 3g/l VOC.

FILM THICKNESS

Wet: 62.5µm, dry: 20µm.

SIZE

5 Litre, 10 Litre & 15 Litre.

KEY PROPERTIES

- Superior trade contract matt ideal for New Build projects
- Excellent high wet & dry opacity
- Easy application with brush, roller or spray
- EU Ecolabel accredited

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray (see below). If more than one can of colour is to be used in the same area, intermix before use. Ensure good ventilation during application and drying. Do not apply in temperatures below 10°C or in damp conditions.

SPRAY & THINNING APPLICATION

Thinning: sealing new or bare surfaces: up to 1.5 part clean water to 10 parts paint @ 2500 PSI / 172 bar with a 517 tip

AIRLESS SPRAY:

Un-thinned: Spray @ 3000 PSI / 207 bar with 517 tip

Thinned: 1 part clean water to 10 parts paint spray @ 2500 PSI / 172 bar with 517 tip

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.