

DESCRIPTION

Johnstone's Dry Lining is a high quality flat matt emulsion specially formulated for application onto bare or primed/sealed Dry Lining boards. It's enhanced opacity and flat matt finish significantly reduces the appearance of surface imperfections in areas featuring critical lighting. It offers excellent coverage and application qualities with a drying time of 1-2 hours making the job easier to complete.

RECOMMENDED USES



Ceiling & walls.

TYPE OF SUBSTRATE

Suitable for use on plasterboard/wallboards/dry lining boards.

COLOUR RANGE

Available in over 6,000 colours via the Johnstone's Tinting System.

FINISH

Matt

VOLUME SOLID

27%

COVERAGE



Johnstone's Dry Lining will cover approximately 12-14 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 2-4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure, upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC Content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010)
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 90µm Dry: 24µm

KEY PROPERTIES

- For use on bare or primed / sealed Dry Lining boards
- Hides surface imperfections highlighted by critical lighting
- Easy to touch up
- Touch dry in 1-2 hours

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. For additional information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal new/bare surfaces with a coat of Dry Lining thinned up to 10% with clean water. Finish with two full coats of Dry Lining paint. Do not apply in temperatures below 10°C.

Plasterboards which have been initially coated with the board manufacturers specified primer/ sealer should also be finish with two coats of Dry Lining paint.

CLEANING / AFTER USE



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents to a Waste Disposal Site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of soap and water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

SIZES

10 Litre.