

**DESCRIPTION**

A solvent-borne protective finish formulated for interior and exterior use. It provides a semi gloss finish that combines excellent opacity with good weather resistance, making it particularly suitable for the long term protection of metal agricultural buildings and structural steel.

**RECOMMENDED USES**

General usage on metal substrates and metal agricultural buildings and structural steel.

**SPECIAL PROPERTIES**

Excellent covering power. Good weather resistance.

**COLOUR RANGE**

Red; Green; Grey.

**FINISH**

Semi gloss.

**VOLUME SOLID**

45%.

**COVERAGE**

Johnstone's Agricultural Oxide will cover at the rate of approximately 14–16 square metres per litre depending on the nature and porosity of the surface being painted.

**DRYING TIME**

Recoat after 16–24 hours under normal drying conditions.

**TRANSPORTATION & STORAGE**

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

**THINNER**

White Spirit.

**VOC CONTENT**

HIGH VOC CONTENT 25–50%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010).  
This product contains max 300g/l VOC.

**FILM THICKNESS**

Wet: 65µm, dry: 30µm.

**SIZE**

5 Litre.

**PREPARATION**

All surfaces to be painted should be clean, dry and free from loose and flaking material. When painting iron and steel remove all millscale and rust. Prime bare surfaces with the appropriate Johnstones Specialist Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory. For additional information and free Johnstones Trade datasheets call 01924 354354 or visit [www.johnstonestrade.com](http://www.johnstonestrade.com)

**APPLICATION**

Stir well. Easy to apply by brush or roller.  
If more than one can of a colour is to be used in the same area, intermix before use.

**CLEANING**

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

**PRECAUTIONS**

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell.
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.
- Safety data sheet available on request.