

DESCRIPTION

Johnstone's Vinyl Silk Emulsion is formulated for interior use on walls and ceilings. It provides a durable sheen finish that is easy to clean and resistant to fading.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Plaster and embossed wallcoverings. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Silk.

VOLUME SOLID

31%

COVERAGE



Approximately 10–12 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 3–4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3–7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/b): 100g/l (2010).
This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 91µm, dry: 28µm.

KEY PROPERTIES

- A high quality vinyl silk finish for interior walls and ceilings.
- Produces a washable surface.
- Especially suitable for embossed wallcoverings and areas where easy maintenance is required.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354354.

APPLICATION



Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Seal absorbent surfaces with a coat of Vinyl Silk thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Safety data sheet available on request.

SIZES

1 Litre, 2.5 Litre, 5 Litre, 10 Litre.