

DESCRIPTION

Johnstone's Ultra Gloss is a premium quality alkyd based gloss developed for interior and exterior use on wood and metal surfaces. It is formulated with excellent opacity, film build and drip resistance, which makes it ideal for new work projects.

RECOMMENDED USES



Suitable for interior and exterior use.

TYPE OF SUBSTRATE

Wood and metal.

COLOUR RANGE

Brilliant white.

FINISH

Gloss.

VOLUME SOLID

62%

COVERAGE



Approximately 17 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME*



Recoat after 16–24 hours under normal drying conditions.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

White Spirit.

VOC CONTENT

High VOC content 25–50%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 300g/l (2010).
This product contains max 300g/l VOC.

FILM THICKNESS

Wet: 60µm, dry: 37µm.

SIZES

1 Litre, 2.5 Litre, 5 Litre.

KEY PROPERTIES

- An alkyd based gloss developed for interior and exterior use on wood and metal surfaces.
- Excellent opacity, film build and drip resistance.
- Ideal for new work projects.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Johnstone's Primer. Rub down previously painted surfaces with fine waterproof abrasive paper and rinse thoroughly to provide a key before applying a pre-coat of Johnstone's Ultra Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory, on 01924 354354.

APPLICATION



Stir well. Easy to apply by brush or roller. Do not apply over polystyrene surfaces.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- **WARNING**
- Flammable liquid and vapour.
- Contains 2-butanone oxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Safety data sheet available on request.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Do not get in eyes, on skin, or on clothing.
- **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- **IF ON SKIN:** Wash with plenty of water. Do not use solvent thinners or White Spirit.
- **IF SWALLOWED:** Call a POISON CENTRE or doctor if you feel unwell
- Ensure maximum ventilation during application and drying.
- Not recommended for interior use on large surface areas, or in confined spaces.
- Store in a well-ventilated place. Keep cool.
- Keep container tightly closed.