

DESCRIPTION

Johnstone's Trade Perfect Matt Wall and Ceiling paint creates a flawless flat matt finish. Innovative Smooth Layer Technology eliminates visible application marks highlighted by critical lighting and provides effortless spot repair.

RECOMMENDED USES

Internal finish for all types of Interior walls and ceilings both bare and previously painted including plaster, plasterboard, concrete, ceiling tiles, wallcoverings etc. Ideal where the surface and site conditions, with critical lighting could combine to be a potential issue.

COLOUR RANGE

Brilliant White, Z Base and L Base.

FINISH

Flat Matt Finish.

VOLUME SOLID

37%

COVERAGE

Up to 13 m² per litre depending on the nature and porosity of the surface.

DRYING TIME

Touch Dry 1 - 2 hour.
Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

Lift with care – gross weight does not exceed 8 kilograms (5L) 16 Kilograms (10L)

Minimise paint wastage by estimating how much paint you will need. Recover unused paint for re-use.

THINNER

Clean water.

VOC CONTENT

EU Limit Value for this product (Cat A/a): 30g/l (2010)

This product contains max 10g/l VOC

LOW VOC CONTENT 0.3 – 7.99%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution

FILM THICKNESS

Wet 100 microns and Dry 37 microns

KEY PROPERTIES

- Eliminates visible application marks
- Flawless matt finish
- Effortless spot repair

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously glossed painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For additional information and free Johnstone's Trade Datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION

Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Do not breathe spray. Wear respiratory protection. Seal absorbent surfaces with a coat of Johnstone's Trade Perfect Matt thinned up to 5-10% with clean water. If more than one can of a colour is to be used in the same area intermix before use. Do not apply in temperatures below 8°C. Use only the original paint for spot repair. Spray Application: AIRLESS SPRAY: Un-thinned: Spray @ 2000 PSI / 207 bar with 517 tip.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings Do not empty product into drains or watercourses Do not use empty container for storing food (10L ONLY)

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available: www.johnstonespaint.com or request from Technical Advisory 01924 354354

SIZES

2.5, 5 and 10 litre